

RESTRICTING ANGLE VALVE

P/N 25-018RUL



P/N 25-022RUL



ADJUSTABLE PRESSURE RESTRICTING ANGLE VALVE

FEMALE x MALE

FUNCTION: Used with a fire hose rack assembly or as a fire dept outlet connection. Water pressure is controlled by adjustable flow restriction. If full flow is required, the restriction may be overridden.

REGULARLY FURNISHED: Cast brass valve with red handwheel with pressure restricting feature. Female NPT inlet x male hose thread outlet. 175 PSI/12 bars rated. Furnished with field setting chart.

Model

4080	1 1/2" / 3.8 cm Size
4085	2 1/2" / 6.4 cm Size

SPECIFY: Thread

OPTIONAL FINISHES:

- B Polished Brass
- C Rough Chrome Plated
- D Polished Chrome Plated

DOUBLE FEMALE

FUNCTION: Used with a fire hose rack assembly. Water pressure is controlled by adjustable flow restriction. If full flow is required, the restriction may be overridden.

REGULARLY FURNISHED: Cast brass valve with red handwheel with pressure restricting feature. Female NPT inlet and outlet. 175 PSI/12 bars rated. Furnished with field setting chart.

Model

4090	1 1/2" / 3.8 cm Size
4095	2 1/2" / 6.4 cm Size

Size	UL Listed	FM Approval	A in. cm	B in. cm	Closed C in. cm	Open C in. cm	D in. cm	E in. cm
1 1/2" / 3.8cm	YES	NO	2 1/4 / 5.7	3 1/2 / 8.9	6 1/2 / 16.5	7 1/2 / 19	2 1/2 / 6.4	2 / 5
2 1/2" / 6.4cm	YES	NO	3 1/2 / 8.9	5 / 12.7	9 1/2 / 24.1	11 1/2 / 29.2	3 1/2 / 8.9	2 3/4 / 6.9

