



## Water And Water Mist

Our Water and Water Mist units provide effective and economical protection for common combustible fires.

Both the Water and Water Mist extinguishers have Schrader Valves incorporated into the Valve Assemblies for easy recharge.

The Water Mist unit uses deionized water and incorporates a unique spray nozzle. These features make it safe for use on energized electrical equipment. Water Mist is considered to be the #1 extinguisher choice for libraries and hospitals.

Water extinguishers are suitable for use on Class A fires. Water Mist is suitable for use on both Class A and Class C fires.

**Typical Uses:** For common combustible fires in offices, classrooms, churches, parking garages, and hotel/motel assembly halls and guest areas. For common combustible fires in businesses such as retail stores, light manufacturing facilities, research facilities, auto dealerships, vehicle/ aircraft/marine service centers, and manufacturing processes such as painting, dipping, and coating.

Model	500	WM250
Part #	50000 (50000 ULC)	51000 (51000 ULC)
Cylinder/Valve Material	Stainless Steel/Plated Brass	Stainless Steel/Plated Brass
Agent Capacity	2.5 gallons (9.6 liters)	2.5 gallons (9.6 liters)
UL/ULC Rating	2-A	2-A:C
Temperature Range	40° to 120°F (4.4° to 49°C)	40° to 120°F (4.4° to 49°C)
Discharge Time	50 sec	73 sec
Discharge Range	45 to 55 ft. (13.7 to 16.8m)	5 to 10 ft. (1.5 to 3m)
Operating Pressure	100 psi (689 kPa)	100 psi (689 kPa)
Mounting Type	Wall	Wall
USCG Approval	Type A Size II	N/A
Ship Weight	Empty: 8.3 lb. (3.7 kg)	Full: 30.25 lb. (13.7 kg)
Unit Height	24.5 in (62.2 cm)	28 in (78.1 cm)
Unit Width (Incl. Hose)	9 in (22.9 cm)	14 in (35.6 cm)
Unit Diameter	7 in (17.8 cm)	7 in (17.8 cm)

Third Party Approvals For Peace Of Mind

