



The model most preferred and specified for Class K fires in Commercial Kitchens

Badger pioneered the use of wet chemical extinguishing agents and equipment technology for commercial kitchen fire protection four decades ago. Badger's innovative design and approach for a safe and effective way to address the various new Class K code requirements back in 1997 has become the industry standard for kitchen hand portable fire extinguishers.

The 6 liter and 2.5 gallon fire extinguisher models are simple to use and extremely effective in handling the difficult types of cooking media fire hazard situations found in today's busy commercial kitchens.

Badger wet chemical hand portable fire extinguisher models are ideally suited to supplement commercial cooking appliance fire suppression systems for addressing tough Class K combustible kitchen cooking media fires.

Features:

- *Heavy-duty chrome plated brass valves*
- *Factory-filled 6 liter model*
- *Operator safe discharge hose concept with non-metal finger guard and protective nozzle orifice seal*
- *Soft 360° mist discharge stream prevents splashing*
- *UL Listed—Meets D.O.T. requirements*
- *Six year warranty*
- *Full stainless steel cylinder, base, handle, lever and pull pin*
- *Hex valve collar tightening ring for easy recharge*
- *Easy-to-read two-piece nameplates*



Technical Data:

BADGER *Extra Wet Chemical Class K Stored Pressure Extinguishers*

| MODEL | WC-100 | WC-250 |
|----------------------------|-------------------|-------------------|
| PART NUMBER | 25064 | 23171 |
| CAPACITY (gallon) | 1.59 | 2.5 |
| CAPACITY (liter) | 6 | 9.46 |
| UL FIRE RATING | K | K |
| AGENT TYPE | Potassium Acetate | Potassium Acetate |
| CYLINDER MATERIAL | Stainless Steel | Stainless Steel |
| VALVE MATERIAL | Plated Brass | Plated Brass |
| HANDLE/LEVER MATERIAL | Stainless Steel | Stainless Steel |
| EXPELLANT | Nitrogen/Air | Nitrogen/Air |
| Operating Pressure @ 70° F | 100 | 100 |
| TEMPERATURE RANGE (° F) | -40 +120 | -40 +120 |
| TEMPERATURE RANGE (° C) | -40 +48.9 | -40 +48.9 |
| AGENT FLOW RATE (lb/sec) | n/a | n/a |
| AGENT FLOW RATE (kg/sec) | n/a | n/a |
| NOM. DISCHARGE TIME (sec) | 50 to 55 | 75 to 80 |
| DISCHARGE RANGE (ft.) | 8.0 to 12.0 | 8.0 to 12.0 |
| DISCHARGE RANGE (m) | 2.4 to 3.7 | 2.4 to 3.7 |
| UNIT HEIGHT (in.) | 19.5 | 24.5 |
| UNIT HEIGHT (cm) | 49.5 | 62.2 |
| UNIT WIDTH (in.) | 8.75 | 8.75 |
| UNIT WIDTH (cm) | 22.2 | 22.2 |
| UNIT DEPTH (in.) | 7 | 7 |
| UNIT DEPTH (cm) | 17.8 | 17.8 |
| SHIPPING WEIGHT (lb.) | 15 | 19 |
| SHIPPING WEIGHT (kg) | 6.8 | 8.6 |
| USCG APPROVAL | n/a | n/a |
| BRACKET | HB-11 Optional | UB-20 Optional |

This information is subject to change without notice. Badger Fire Protection disclaims any liability for any errors or misinterpretations of the information contained therein. Contact Badger Fire Protection for your local distributor for assistance.

Distributed by:

ABRASIL CO INC
T. 507-260-9061 // 236-5644
abrasil@cwpanama.net

Badger Fire Protection
944 Glenwood Station Lane, Suite 303
Charlottesville, VA 22901
Tel.: 434.964.3200 • Fax: 434.964.3202
www.badgerfire.com

SS B-010
All Rights Reserved.

May 2013

