



Halotron

Halotron is a clean, non conductive gaseous agent that is an excellent replacement for Halon 1211 extinguishers. Halotron is suitable for use on Class A, Class B and Class C fires.

Typical Uses: For protecting sensitive electronic equipment in offices, classrooms, churches, parking garages, and hotel/motel assembly halls and guest areas. For protecting sensitive electronic equipment in businesses such as retail stores, light manufacturing facilities, research facilities, auto dealerships, vehicle/aircraft/marine service centers, and manufacturing processes such as painting, dipping, and coating.

Recommended for use on sensitive electronic equipment.

Third Party Approvals For Peace Of Mind



Canadian Part Numbers are shown in parentheses. V/B = Vehicle Bracket Included. F = Fixed Nozzle. H = Hose.

Model	2.5F	2.5F V/B	2.5H	2.5H V/B	5F	5F V/B	5H	5H V/B	11	15
Pt. # Alum. Value	70258 (70280)	70251 (70295)	70259 (70260)	70256 (70265)	70510 (70580)	70550 (70590)	75550 (75560)	75555 (75565)	71100 (71180)	71550 (71580)
Pt. # Brass Value	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	71101 (71181)	71551 (71581)
Agent Capacity	2.5 lb. (1.13 kg)	2.5 lb. (1.13 kg)	2.5 lb. (1.13 kg)	2.5 lb. (1.13 kg)	5 lb. (2.27 kg)	5 lb. (2.27 kg)	5.5 lb. (2.49 kg)	5.5 lb. (2.49 kg)	11 lb. (5 kg)	15.5 lb. (7.03 kg)
UL/ULC Rating	2-B:C	2-B:C	2-B:C	2-B:C	5-B:C	5-B:C	5-B:C	5-B:C	1-A:10-B:C	2-A:10-B:C
Temperature Range	-40° to 120°F (-40° to 49°C)									
Discharge Time	9 sec	9 sec	9 sec	9 sec	9 sec	9 sec	9 sec	9 sec	9 sec	13 sec
Discharge Range ft (m)	6-10 (1.8-3)	6-10 (1.8-3)	6-10 (1.8-3)	6-10 (1.8-3)	9-15 (2.7-4.5)	9-15 (2.7-4.5)	9-15 (2.7-4.5)	9-15 (2.7-4.5)	9-15 (2.7-4.5)	12-18 (3.7-5.5)
Operating Pressure	100 psi (689 kPa)	100 psi (689 kPa)	100 psi (689 kPa)	100 psi (689 kPa)	100 psi (689 kPa)	100 psi (689 kPa)	100 psi (689 kPa)	100 psi (689 kPa)	100 psi (689 kPa)	125 psi (862 kPa)
Mounting Type	Wall	Vehicle	Wall	Vehicle	Wall	Vehicle	Wall	Vehicle	Wall	Wall
USCG Approval	N/A	N/A	N/A	N/A	N/A	Type B:C Size I	N/A	Type B:C Size I	Type B:C Size I	Type B:C Size II
Ship Weight	5.25 lb. (2.4 kg)	5.5 lb. (2.49 kg)	5.5 lb. (2.49 kg)	5.75 lb. (2.6 kg)	9.25 lb. (4.2 kg)	9.5 lb. (4.3 kg)	10.0 lb. (4.5 kg)	10.25 lb. (4.7 kg)	21.25 lb. (9.6 kg)	25.75 lb. (11.75 kg)
Unit Height	13.375 in (34 cm)	13.375 in (34 cm)	13.375 in (34 cm)	13.375 in (34 cm)	16.375 in (41.6 cm)	16.375 in (41.6 cm)	16.375 in (41.6 cm)	16.375 in (41.6 cm)	17.5 in (44.5 cm)	17.5 in (44.5 cm)
Unit Width	5.625 in (14.3 cm)	5.625 in (14.3 cm)	6.75 in (17.1 cm)	6.75 in (17.1 cm)	6.5 in (16.5 cm)	7.25 in (18.5 cm)	6.5 in (16.5 cm)	7.25 in (18.5 cm)	8.625 in (21.9 cm)	8.625 in (21.9 cm)
Unit Diameter	3.375 in (8.6 cm)	3.375 in (8.6 cm)	3.375 in (8.6 cm)	4.25 in (10.8 cm)	4.25 in (10.8 cm)	4.25 in (10.8 cm)	4.25 in (10.8 cm)	4.25 in (10.8 cm)	7 in (17.8 cm)	7 in (17.8 cm)